



**SELECT** ✓

**SELECT<sub>80</sub>** ✓



<b>Roll Size</b>	76" x 100' 76" x 600' (nominal) Cut to size	76" x 100' 76" x 600' (nominal) Cut to size	76" x 100' 76" x 600' (nominal) Cut to size	76" x 100' 76" x 600' (nominal) Cut to size
<b>Thickness</b>	60 mil (nominal)	60 mil (nominal)	80 mil (nominal)	80 mil (nominal)
<b>UV Stability</b>	5000 hrs weathering	5000 hrs weathering	5000 hrs weathering	5000 hrs weathering
<b>Tensile Strength</b>	ASTM D751	Meets & exceeds requirements for PVC roofing membrane outlined in CAN/ CGSB 37-54-95 and ASTM 4434-04	Meets & exceeds requirements for PVC roofing membrane outlined in CAN/ CGSB 37-54-95 and ASTM 4434-04	Meets & exceeds requirements for PVC roofing membrane outlined in CAN/ CGSB 37-54-95 and ASTM 4434-04
<b>Wear Resistance</b>	ASTM C501-84	Meets & exceeds requirements for PVC roofing membrane outlined in CAN/ CGSB 37-54-95 and ASTM 4434-04	Meets & exceeds requirements for PVC roofing membrane outlined in CAN/ CGSB 37-54-95 and ASTM 4434-04	Meets & exceeds requirements for PVC roofing membrane outlined in CAN/ CGSB 37-54-95 and ASTM 4434-04
<b>Fire Rating</b>	Can/ULC- S107-M87/UL 790 Class C	Class A* *over a non- combustible substrate	Class A* *over a non- combustible substrate	Class A* *over a non- combustible substrate
<b>Fade Resistant</b>	UV Stabilized	UV Stabilized	UV Stabilized	UV Stabilized
<b>Mildew/Mold Resistant</b>	Anti-microbial	Anti-microbial	Anti-microbial	Anti-microbial
<b>Warranty</b>	10 Year	10 Year	20 Year	20 Year
<b>Colours</b>	» Brick 7501	✓	✓	
	» Granite 6642	✓	✓	✓
	» Bronze 7504	✓	✓	✓
	» Opal 6642	✓	✓	
	» Cool White			